

Certificate

Registration No.: PV 60039386

Page 1

Report No.: 21169470.001

License Holder:
Scheuten Solar Logistics B.V.
Van Heemskerckweg 30
5928 LL Venlo
The Netherlands

Manufacturing plant:
Scheuten Solar Technology GmbH
Scheuten-Solar-Straße 2
45842 Gelsenkirchen
Germany

Product:
PV Modules
Type:
Multisol® P6-66, Multisol® M6-66
(power range 225-265 Wp in steps of 5 Wp)
Multisol® P6-60, Multisol® M6-60
(power range 200-240 Wp in steps of 5 Wp)
Multisol® P6-54
(power range 180-210 Wp in steps of 5 Wp)
Multisol® M6-54
(power range 185-215 Wp in steps of 5 Wp)
Multisol® P6-48, Multisol® M6-48
(power range 160-195 Wp in steps of 5 Wp)
Multisol® P5-96
(power range 200-235 Wp in steps of 5 Wp)
Multisol® M5-96
(power range 210-250 Wp in steps of 5 Wp)

Basis:

IEC 61215:2005
EN 61215:2005
"Crystalline silicon terrestrial
photovoltaic (PV) modules - Design
qualification and type approval"

Factory Inspection
To document the consistent quality of
the product factory inspections are
performed periodically.



- Qualified, IEC 61215
- Periodic inspection

Remarks:

- The details of the factory inspection are documented in report no.: 21214886.

Conditions:

The product test is voluntarily according to technical regulations. Any change of the design, materials, components or processing may require the repetition of some of the qualification tests in order to retain type approval.

The certificate is valid until 10 August 2014.



Cologne, 27 May 2011

Dipl.-Ing. M. Adrian

Certificate

Registration No.: PV 60039386

Page 2

Report No.: 21169470.001

License Holder:
Scheuten Solar Logistics B.V.
Van Heemskerckweg 30
5928 LL Venlo
The Netherlands

Manufacturing plant:
Scheuten Optisol B.V.
Van Heemskerckweg 30
5928 LL Venlo
The Netherlands

Product:
PV Modules
Type:
Multisol® P6-66, Multisol® M6-66
(power range 225-265 Wp in steps of 5 Wp)
Multisol® P6-60, Multisol® M6-60
(power range 200-240 Wp in steps of 5 Wp)
Multisol® P6-54
(power range 180-210 Wp in steps of 5 Wp)
Multisol® M6-54
(power range 185-215 Wp in steps of 5 Wp)
Multisol® P6-48, Multisol® M6-48
(power range 160-195 Wp in steps of 5 Wp)
Multisol® P5-96
(power range 200-235 Wp in steps of 5 Wp)
Multisol® M5-96
(power range 210-250 Wp in steps of 5 Wp)

Basis:

IEC 61215:2005
EN 61215:2005
"Crystalline silicon terrestrial photovoltaic (PV) modules - Design qualification and type approval"

Factory Inspection
To document the consistent quality of the product factory inspections are performed periodically.



- Qualified, IEC 61215
- Periodic inspection

Remarks:

- The details of the factory inspection are documented in report no.: 21211829.

Conditions:

The product test is voluntarily according to technical regulations. Any change of the design, materials, components or processing may require the repetition of some of the qualification tests in order to retain type approval.
The certificate is valid until 10 August 2014.



Cologne, 27 May 2011

Dipl.-Ing. M. Adrian